

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/731,259	12/05/2003	Rumi Sheryar Gonda	RGQ-005	4710
959	7590 11/03/2005		EXAMINER	
LAHIVE & COCKFIELD, LLP.			DAVIS, CYNTHIA L	
28 STATE S BOSTON, M			ART UNIT	PAPER NUMBER
,			2665	
			DATE MAILED: 11/03/2009	5

Please find below and/or attached an Office communication concerning this application or proceeding.

	y						
	Application No.	Applicant(s)					
	10/731,259	GONDA, RUMI SHERYAR					
Office Action Summary	Examiner	Art Unit					
	Cynthia L. Davis	2665					
The MAILING DATE of this communication app Period for Reply	pears on the cover sheet v	rith the correspondence address					
A SHORTENED STATUTORY PERIOD FOR REPL' THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.1: after SIX (6) MONTHS from the mailing date of this communication. - If the period for reply specified above is less than thirty (30) days, a reply If NO period for reply is specified above, the maximum statutory period v - Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	. 36(a). In no event, however, may a ywithin the statutory minimum of the vill apply and will expire SIX (6) MC, cause the application to become A.	reply be timely filed rty (30) days will be considered timely. NTHS from the mailing date of this communication. BANDONED (35 U.S.C. § 133).					
Status							
1) Responsive to communication(s) filed on 14 S	eptember 2005.						
2a)⊠ This action is FINAL . 2b)☐ This	action is non-final.						
	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.						
Disposition of Claims							
4) ☐ Claim(s) 1-4 and 6-46 is/are pending in the appear 4a) Of the above claim(s) is/are withdraw 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1-4 and 6-46 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/o	wn from consideration.						
Application Papers							
9) The specification is objected to by the Examine							
10) The drawing(s) filed on is/are: a) acce							
Applicant may not request that any objection to the		, ,					
Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the Ex	•	• • •).				
Priority under 35 U.S.C. § 119							
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority documents 2. Certified copies of the priority documents 3. Copies of the certified copies of the priority application from the International Bureau * See the attached detailed Office action for a list	s have been received. s have been received in a rity documents have been u (PCT Rule 17.2(a)).	Application No n received in this National Stage					
Attachment(s)							
Notice of References Cited (PTO-892)		Summary (PTO-413)					
2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date		s)/Mail Date Informal Patent Application (PTO-152)					

Art Unit: 2665

DETAILED ACTION

Response to Arguments

1. Applicant's arguments filed 9/14/2005 have been fully considered but they are not persuasive.

Regarding claim 41, the applicant admits in the specification that APS is SDH/SONET functionality. Hence, any bridge providing APS is providing a SDH/SONET-type bridge. The device of Yip provides APS, which reads on the amended claims.

Regarding claim 42, the switch of Yip is the same as the selector recited in the claim, see the instant specification, page 8, line 26. Further, blocking or unblocking the secondary port is equivalent to selecting or unselecting the protect channel.

Regarding claim 44, there are a plurality of PHY devices on any typical network; the bridge interfaces all of them.

Regarding claim 1, the switch of Yip is the same as the selector recited in the claim, see the instant specification, page 8, line 26. Further, blocking or unblocking the secondary port is equivalent to selecting or unselecting the protect channel. Further, there are a plurality of PHY devices on any typical network; the bridge interfaces all of them.

Regarding claim 30, the applicant admits in the specification that APS is SDH/SONET functionality. Hence, any bridge providing APS is providing a SDH/SONET-type bridge. The device of Yip provides APS, which reads on the amended claims.

Regarding claim 35, the switch of Yip is the same as the selector recited in the claim, see the instant specification, page 8, line 26. Further, there are a plurality of PHY devices on any typical network; the selector interfaces all of them.

Claim Rejections - 35 USC § 112

The following is a quotation of the first paragraph of 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

2. Claims 1, 30, 35, 41, 42, and 44 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention. The specification discloses a bridge, used in an Ethernet environment, that provides APS functionality, APS being a function normally associated with SDH/SONET. It does not disclose an SDH/SONET bridge such as is recited in the amended claims.

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

Page 4

Regarding claim 41, a method of providing SDH/SONET APS functionality on an Ethernet protocol network, comprising the steps of: configuring an Ethernet APS Bridge Selector in bridge mode to provide a SDH/SONET bridge; and bridging transmit traffic to working and protect channels on an Ethernet protocol network is disclosed in Yip, column 2, lines 12-26 (disclosing EAPS bridging functionality; APS is a functionality of SONET, so the bridge working as a SONET bridge, see the instant specification, page 2, lines 21-22).

Regarding claim 42, a method of providing SDH/SONET APS functionality on an Ethernet protocol network, comprising the steps of: configuring an Ethernet APS Bridge Selector in selector mode to provide a SDH/SONET selector on an Ethernet protocol network; selecting receive traffic from at least one of working or protect channels, and switching from an active channel to one of a standby channel or a specified channel when requested is disclosed in Yip, column 2, lines 12-26 (disclosing EAPS switching functionality, switching being an alternate term for selector, see the instant specification, page 8, line 26. Also, APS is a functionality of SONET, so the selector is working as a SONET selector, see the instant specification, page 2, lines 21-22).

Regarding claim 44, a method of providing SDH/SONET APS functionality on an Ethernet protocol network comprising the steps of: one of bridging or selecting, by an EAPS Bridge Selector implementing SDH/SONET APS on an Ethernet protocol network, between a MAC hardware device and a plurality of PHY hardware devices,

and switching by the Ethernet APS bridge selector, over from an active channel to one of a standby channel and a specified channel when requested is disclosed in Yip, column 2, lines 12-26 (disclosing EAPS and both bridging and switching functionality, switching being an alternate term for selector, see the instant specification, page 8, line 26. Also, APS is a functionality of SONET, so the selector is working as a SONET selector, see the instant specification, page 2, lines 21-22).

Claim Rejections - 35 USC § 103

The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.

4. Claims 1-4, 6-9, 15-19, 23, 26-28, 30, and 35 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yip in view of Laber.

Regarding claim 1, an Ethernet APS Bridge Selector for implementing SDH/SONET APS in an Ethernet environment, the Ethernet APS Bridge selector providing one of a SDH/SONET Bridge or a SDH/SONET selector is disclosed in Yip, column 2, lines 12-26 (disclosing EAPS and both bridging and switching functionality, switching being an alternate term for selector, see the instant specification, page 8, line 26. Also, APS is a functionality of SONET, so the selector is working as a SONET selector, see the instant specification, page 2, lines 21-22). An Ethernet APS Bridge Selector Sublayer for managing the Ethernet APS Bridge Selector wherein the Ethernet APS Bridge Selector interconnects Media Access Control (MAC) hardware and a plurality of Physical Layer (PHY) hardware devices is missing from Yip. However, Laber discloses in column 1, lines 61-63, a bridge connecting MAC and PHY layers. It would

Page 6

have been obvious to one skilled in the ad at the time of the invention to have the Ethernet APS Bridge selector interconnect the MAC and PHY hardware. The motivation would be to allow the physical devices to communicate with the network via the MAC.

Regarding claim 2, the MAC interfaces with the Ethernet APS Bridge Selector is disclosed in Yip, column 4, line 21.

Regarding claim 3, the Ethernet APS Bridge Selector interfaces with the plurality of PHY hardware devices is missing from Yip. However, Laber discloses in column 1, lines 61-63, a bridge connecting to the PHY layer. It would have been obvious to one skilled in the art at the time of the invention to have the Ethernet APS Bridge selector connect to the PHY hardware. The motivation would be to allow the physical devices to communicate with the network via the MAC.

Regarding claim 4, the Ethernet APS Bridge Selector enables Standard SDH/SONET APS functionality in an Ethernet Architecture is disclosed in Yip, column 2, lines 5-7.

Regarding claim 6, the Ethernet APS Bridge Selector comprises at least one of a bridge and a selector is disclosed in Yip, column 2, lines 12-26 (disclosing EAPS and both bridging and switching functionality, switching being an alternate term for selector, see the instant specification, page 8, line 26).

Regarding claim 7, the Ethernet APS Bridge Selector executes bridging operations is disclosed in Yip, column 3, lines 12-19 (disclosing bridging traffic to the protection channel).

Art Unit: 2665

Regarding claim 8, the Ethernet APS Bridge Selector executes selector operations is disclosed in Yip, column 2, lines 12-26 (disclosing switching functionality, switching being an alternate term for selector, see the instant specification, page 8, line 26).

Regarding claim 9, the Ethernet APS Bridge Selector executes switching operations is disclosed in Yip, column 2, lines 12-26 (disclosing switching functionality).

Regarding claim 15, the Ethernet APS Bridge Selector interfaces the PHY using a MAC to PHY interconnect interface is missing from Yip. However, Laber discloses in column 1, lines 61-63, a bridge interfacing MAC and PHY layers. It would have been obvious to one skilled in the art at the time of the invention to use a MAC to PHY interconnect interface in the Ethernet APS Bridge selector to interconnect the MAC and PHY hardware. The motivation would be to allow the physical devices to communicate with the network via the MAC.

Regarding claim 16, the Ethernet APS Bridge Selector bridges between the plurality of PHY hardware devices is disclosed in Yip, column 3, lines 12-19 (disclosing bridging traffic to the protection channel).

Regarding claim 17, the Ethernet APS Bridge Selector selects between the plurality of PHY hardware devices is disclosed in Yip, column 2, lines 12-26 (disclosing switching functionality, switching being an alternate term for selector, see the instant specification, page 8, line 26).

Regarding claim 18, the Ethernet APS Bridge Selector switches between the plurality of PHY hardware devices is disclosed in Yip, column 2, lines 12-26 (disclosing switching functionality).

Regarding claim 19, the Ethernet APS Bridge Selector provides switchover within 50 ms for recovery and protection functionality is missing from Yip. However, the instant specification discloses on page 3, line 10, that 50ms is the standard switchover time for SDH/SONET. It would have been obvious to one skilled in the ad at the time of the invention to have the bridge selector provide switchover within 50ms. The motivation would be to have the instant invention be as fast as SDH/SONET APS.

Regarding claim 23, the Ethernet APS Bridge Selector is one of unidirectional and bidirectional is missing from Yip. However, Laber discloses in column 1, lines 64-65, bidirectional bridge. It would have been obvious to one skilled in the art at the time of the invention to use a bidirectional bridge in the invention of Yip. The motivation would be to allow simultaneous communication (Laber, column 1, lines 63-64).

Regarding claim 26, the Ethernet APS Bridge Selector is controlled by a MAC Client in the form of at least one of APS and OAMP is disclosed in Yip, column 2, lines 5-6 (disclosing APS) and column 4, line 21 (disclosing MAC).

Regarding claim 27, the Ethernet APS Bridge Selector is controlled by software in the form of at least one of APS Controller software and OAMP software is disclosed in Yip, column 8, lines 20-25 (disclosing APS software).

The Control Hamber: 10/10/1,20

Art Unit: 2665

Regarding claim 28, hardware implementing a plurality of Ethernet APS Bridge Selector devices is disclosed in Yip, 8, lines 51-54 (disclosing the invention being implemented in a multiple node/switch network, which would require multiple devices).

Regarding claim 30, providing a Bridge Selector APS sublayer and configuring the Bridge Selector APS sublayer in a bridge mode for providing SDH/SONET bridging functionality is disclosed in Yip, column 2, lines 12-26 (disclosing EAPS and bridging functionality. Also, APS is a functionality of SONET, so the bridge is working as a SONET bridge, see the instant specification, page 2, lines 21-22). Bridging a MAC hardware device to a plurality of PHY hardware devices, wherein the Bridge Selector APS sublayer interfaces to MAC transmit signals and bridges signals to a plurality of PHY transmit signals is missing from Yip. However, Laber discloses in column 1, lines 61-63, a bridge connecting MAC and PHY layers. It would have been obvious to one skilled in the art at the time of the invention to have the Ethernet APS Bridge selector interconnect the MAC and PHY hardware. The motivation would be to allow the physical devices to communicate with the network via the MAC.

Regarding claim 35, configuring a Bridge Selector APS Sublayer in selector mode for providing SDH/SONET Selector functionality and switching over from an active channel to one of a standby channel and a specified channel when requested is disclosed in Yip, column 2, lines 12-26 (disclosing EAPS and switching functionality, switching being an alternate term for selector, see the instant specification, page 8, line 26. Also, APS is a functionality of SONET, so the selector is working as a SONET selector, see the instant specification, page 2, lines 21-22). The Bridge Selector APS

Sublayer selecting from the plurality of PHY hardware devices for connection to the MAC hardware device and the Bridge Selector APS Sublayer interfacing to a plurality pf PHY receive signals and selecting signals to MAC receive signals is missing from Yip. However, Laber discloses in column 1, lines 61-63, a bridge connecting MAC and PHY layers. It would have been obvious to one skilled in the art at the time of the invention to have the Ethernet APS Bridge selector interconnect the MAC and PHY hardware. The motivation would be to allow the physical devices to communicate with the network via the MAC.

5. Claims 10, 11, 34, and 39 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yip in view of Laber in further view of Lu.

Regarding claim 10, the Ethernet APS Bridge Selector enables drop and continue functionality is missing from Yip. However, Lu discloses in column 9, line 46, that drop-continue is a type of cross connection used in APS. It would have been obvious to one skilled in the ad at the time of the invention to implement drop and continue in the system of Yip. The motivation would be to implement full APS functionality.

Regarding claim 11, the Ethernet APS Bridge Selector enables pass through functionality is missing from Yip. However, Lu discloses in column 9, line 47, that passing through is a type of cross connection used in APS. It would have been obvious to one skilled in the ad at the time of the invention to implement pass through in the system of Yip. The motivation would be to implement full APS functionality.

Art Unit: 2665

Regarding claim 34, the Bridge Selector APS sublayer comprises a bridge configured to be in pass through mode wherein an input interface passes through to an output interface is missing from Yip. However, Lu discloses in column 9, line 47, that passing through is a type of cross connection used in APS. It would have been obvious to one skilled in the ad at the time of the invention to implement pass through in the system of Yip. The motivation would be to implement full APS functionality.

Regarding claim 39, the Bridge Selector APS Sublayer comprises a bridge configured to be in pass through mode, wherein an input interface passes through to output interfaces is missing from Yip. However, Lu discloses in column 9, line 47, that passing through is a type of cross connection used in APS. It would have been obvious to one skilled in the art at the time of the invention to implement pass through in the system of Yip. The motivation would be to implement full APS functionality.

6. Claims 12, 14, 29, 33, and 38 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yip in view of Laber in further view of Sefidvash.

Regarding claim 12, the Ethernet APS Bridge Selector interfaces with a MAC using RS interface primitives is missing from Yip. However, Sefidvash discloses in paragraph 31 a MAC that uses an RS interface. It would have been obvious to one skilled in the art at the time of the invention to use and RS interface. The motivation would be to reconcile the sublayers.

Regarding claim 14, the Bridge Selector Sublayer interface comprises an Attachment Unit Interface (AUI) in the form of XAUI is missing from Yip. However, Sefidvash discloses a XAUI interface between a MAC and a PHY in paragraph 30. It

would have been obvious to one skilled in the art at the time of the invention to use a XAUI interface in the Bridge Selector. The motivation would be to use a fast type of interface (Sefidvash, paragraph 17).

Regarding claim 29, the Ethernet APS Bridge Selector devices are implemented in at least one of a MAC, XGXS, XAUI, and PHY hardware device is missing from Yip. However, Sefidvash discloses a XAUI interface between a MAC and a PHY in paragraph 30. It would have been obvious to one skilled in the art at the time of the invention to use a XAUI interface hardware device for the Bridge-Selector. The motivation would be to use a fast type of interface (Sefidvash, paragraph 17).

Regarding claim 33, the Bridge Selector APS Sublayer interface comprises an AUI in the form of XAUI is missing from Yip. However, Sefidvash discloses a XAUI interface between a MAC and a PHY in paragraph 30. It would have been obvious to one skilled in the art at the time of the invention to use a XAUI interface in the Bridge Selector. The motivation would be to use a fast type of interface (Sefidvash, paragraph. 17).

Regarding claim 38, the Bridge Selector APS Sublayer interface comprises an AUI in the form of XAUI is missing from Yip. However, Sefidvash discloses a XAUI interface between a MAC and a PHY in paragraph 30. It would have been obvious to one skilled in the art at the time of the invention to use a XAUI interface in the Bridge Selector. The motivation would be to use a fast type of interface (Sefidvash, paragraph 17).

Art Unit: 2665

7. Claims 13, 21, 32 and 37 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yip in view of Laber in further view of Shi.

Regarding claim 13, the Bridge Selector Sublayer interface comprises a PHY interface in the form of one of XGMII, GMII, and MII is missing from Yip. However, Shi discloses in column 1, lines 26-27, that XGMII is a standard interface between MAC and PHY. It would have been obvious to one skilled in the art at the time of the invention to use XGMII in the invention of Yip. The motivation would be to use a standard interface.

Regarding claim 21, the Ethernet APS Bridge Selector provides signals in the form of one of XGMII and XAUI, to control APS functionality is missing from Yip. However, Shi discloses in column 1, lines 26-27, that XGMII is a standard interface between MAC and PHY. It would have been obvious to one skilled in the art at the time of the invention to use XGMII in the invention of Yip. The motivation would be to use @ standard interface.

Regarding claim 32, the Bridge Selector APS Sublayer interface comprises an MII interface in the form of at least one of XGMII, GMII, and MII is missing from Yip. However, Shi discloses in column 1, lines 26-27, that XGMII is a standard interface between MAC and PHY. It would have been obvious to one skilled in the ad at the time of the invention to use XGMII in the invention of Yip. The motivation would be to use a standard interface.

Regarding claim 37, the Bridge Selector APS Sublayer interface comprises an MII interface in the form of at least one of XGMII, GMII, and MII is missing from Yip.

However, Shi discloses in column 1, lines 26-27, that XGMII is a standard interface between MAC and PHY. It would have been obvious to one skilled in the ad at the time of the invention to use XGMII in the invention of Yip. The motivation would be to use a standard interface.

8. Claim 22 is rejected under 35 U.S.C. 103(a) as being unpatentable over Yip in view of Laber in further view of Abbott.

Regarding claim 22, the Ethernet APS Bridge Selector provides control/register interfaces to control APS functionality is missing from Yip. However, a control register interface is disclosed in Abbott, column 51, line 4. It would have been obvious to one skilled in the art at the time of the invention to use a control register interface. The motivation would be to control a serial bus for communication among various hardware devices (Abbott, column 51, lines 3-5).

9. Claims 20, 31, and 36 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yip in view of Laber in further view of Lurndal.

Regarding claim 20, the Ethernet APS Bridge Selector provides a PLS interface to control APS functionality is missing from Yip. However, Lurndal discloses in column 19, lines 54-55, a PLS interface. It would have been obvious to one skilled in the art at the time of the invention to include a PLS interface in the invention of Yip. The motivation would be to maintain port localization information (Lurndal, column 19, lines 56-57).

Regarding claim 31, the Bridge Selector APS Sublayer interface comprises an RS interface in the form of PLS is missing from Yip. However, Lurndal discloses in

column 19, lines 54-55, a PLS interface. It would have been obvious to one skilled in the art at the time of the invention to include a PLS interface in the invention of Yip. The motivation would be to maintain port localization information (Lurndal, column 19, lines 56-57).

Regarding claim 36, the Bridge Selector APS Sublayer interface comprises an RS interface in the form of PLS is missing from Yip. However, Lurndal discloses in column 19, lines 54-55, a PLS interface. It would have been obvious to one skilled in the art at the time of the invention to include a PLS interface in the invention of Yip. The motivation would be to maintain port localization information (Lurndal, column 19, lines 56-57).

- 10. Claim 24 is rejected under 35 U.S.C. 103(a) as being unpatentable over Yip in view of Laber in further view of Taketomi. The Ethernet APS Bridge Selector is utilized in at least one of nested and non-nested combinations is missing from Yip. However, Taketomi discloses in column 10, lines 59-60, a nested switching system. It would have been obvious to one skilled in the art to utilize the invention of Yip in a nested combination. The motivation would be to switch lines in every section of the system (Taketomi, column 10, lines 57-58).
- 11. Claim 25 is rejected under 35 U.S.C. 103(a) as being unpatentable over Yip in view of Laber in further view of Burnett. A plurality of MAC sublayers that control the Ethernet APS Bridge Selector is missing from Yip. However, Burnett discloses in column 7 a plurality of MAC sublayers in a bridged network, for the purpose of interfacing with a wide variety of media. It would have been obvious to one skilled in the

art at the time of the invention to have multiple MAC sublayers in the invention of Yip.

The motivation would be to interface with a wide variety of media.

12. Claims 40, 43, and 46 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yip in view of the admitted prior art.

Regarding claim 40, the step of switching over executes within 50 ms to provide recovery functionality on an Ethernet protocol network is missing from Yip. However, the instant specification discloses on page 3, line 10, that 50mà is the standard switchover time for SDH/SONET. It would have been obvious to one skilled in the art at the time of the invention to have the bridge selector provide switchover within 50ms. The motivation would be to have the instant invention be as fast as SDH/SONET APS.

Regarding claim 43, the method executes within 50 ms to provide recovery functionality is missing from Yip. However, the instant specification discloses on page 3, line 10, that 50ms is the standard switchover time for SDH/SONET. It would have been obvious to one skilled in the art at the time of the invention to have the bridge selector provide switchover within 50ms. The motivation would be to have the instant invention be as fast as SDH/SONET APS.

Regarding claim 46, the method executes within 50 ms to provide recovery functionality is missing from Yip. However, the instant specification discloses on page 3, line 10, that 50ms is the standard switchover time for SDH/SONET. It would have been obvious to one skilled in the art at the time of the invention to have the bridge selector provide switchover within 50ms. The motivation would be to have the instant invention be as fast as SDH/SONET APS.

13. Claim 45 is rejected under 35 U.S.C. 103(a) as being unpatentable over Yip in view of Abbot. The method enables standard SDH/SONET APS functionality for linear, ring, and mesh topologies for Ethernet protocol networks is disclosed in Yip, column 1, lines 40 (disclosing linear, i.e., a bus network), column 2, line 7, and column 7, lines 42-48 (disclosing mesh; the invention is designed to prevent loops in mesh networks as well). Using signals is disclosed in column 8, line 39. Using control/register interfaces is missing from Yip. However, a control register interface is disclosed in Abbott, column 51, line 4. It would have been obvious to one skilled in the art at the time of the invention to use a control register interface. The motivation would be to control a serial bus for communication among various hardware devices (Abbott, column 51, lines 3-5).

Conclusion

THIS ACTION IS MADE FINAL. Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Art Unit: 2665

Page 18

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Cynthia L. Davis whose telephone number is (571) 272-3117. The examiner can normally be reached on 8:30 to 6, Monday to Thursday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Huy Vu can be reached on (571) 272-3155. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

CLD 10/19/2005

HUY D. VU

SUPERVISORY PATENT EXAMINÉR TECHNOLOGY CENTER 2600